

PUFAS Full-Tone and Tinting Paints Painter's Quality

PUFAS Vollton- und Abtönfarbe Maler Qualität

- for high-opacity coatings and for tinting emulsion paints and other water-based materials
- excellent miscibility
- high tinting strength
- wet-scrub resistance class 2 to EN 13300
- lightfast and UV-stable
- suitable for airless spray application
- for indoor and outdoor use

Instructions for use:

Tinting paints are suitable for modern paint designs for façades and living space as well as for shading standard commercial, water-based emulsion, dispersion, latex, wall and ceiling paints and also for synthetic resin plasters and plastic.

The colours 506, 507, 508, 510, 511, 513, 521, 526, 550, 551, 553 and 554 are also suitable for tinting silicate paints, whereby the amount added should not exceed 10 %. Observe the EN standard.

Technical specifications:

Components: Synthetic resin emulsion, coloured pigments
 Density: approx. 1.3 g/cm³
 pH-value: approx. 8.5
 Gloss Unit: matt
 Usage: 150-200 ml/m² per coat

Substrate preparation:

The surface must be dry, firm, dust and grease free. Remove old, peeling wallpapers and flaking coats of paint using decotric Wallpaper Remover. Make good cracks and holes using pufamur Interior Super Bonding Filler SH 45 or pufamur Exterior Filler AKS. Prime highly sanding, absorbent and chalking surfaces with PUFAS Deeply-Penetrating Primer LF - solvent free or LH.

Application:

Tinting paints can be applied with a brush, paint roller or a suitable spray gun. For undercoats the paints can be thinned with max. 10 % water. Apply the topcoat unthinned or with max. 5 % water added.

To tint white emulsion paints, stir in Tinting paints until the mix is homogeneous and use according to the instructions. Adding large quantities of Tinting paints to white, glossy emulsion paints can cause a reduction in the gloss. It is necessary to use the same white basic paint to achieve the same shade when remixing paint.

Due to their high organic pigment content, full colour paints in the colours sun yellow, orange, bright red and mint have a low hiding power. Adding 5-10 % white emulsion paint increases the hiding power. Only use the colours marked in the colour cards with an asterisk (*) in full colour for outdoors.

Do not use if the surface and/or room temperature are less than + 5° Celsius!

Clean tools in water immediately after use. The laying instructions of the floor covering manufacturers must be complied with.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the surface and/or room temperature are less than + 5° Celsius!

Clean tools in water immediately after use.

The laying instructions of the floor covering manufacturers must be complied with.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool but frost-free place! Keep the containers tightly sealed!

Available sizes:

250 ml	05xx03000	REG
750 ml	05xx04000	REG
5 l	05xx05000	REG