

## PUFAS Glassfibre and Non-Woven Wallpaper Adhesive PUFAS Glasgewebe- und Vlieskleber GK

Instructions for use:	PUFAS Glassfibre and Non-Woven Wallpaper Adhesive is suitable for hanging non-woven wallpapers, Glassfibre wallpapers as well as renovation fleece.				
Technical information:	Components:		Ilulose, starch ether, resin powder		
	Density:	approx. 0	.45 g/cm <sup>3</sup>		
	pH-value:	approx. 8	3		
	Usage:	approx. 2	approx. 200 g/m <sup>2</sup>		
Surface preparation:	The surface must be dry, firm and free of dust and grease. Remove old, peeling wallpapers and distemper paints using <i>PUFAS Wallpaper Remover</i> . Make good cracks and holes using <i>PUFAS interior</i> or <i>PUFAMUR Super Bonding Filler</i> . Prime highly absorbent, sanding and chalking surfaces with <i>PUFAS Deeply-Penetrating Primer – solvent free</i> .				
	Insulate water-soluble impurities, which may show through when wallpapering with <i>PUFAS Insulating Spray White</i> .				
Application:	Stirring vigorously, sprinkle <i>PUFAS Glassfibre and Non-Woven Wallpaper Ad-</i> <i>hesive</i> into clean, cold water (see table) and continue to stir for a few minutes. Leave for approx 15 minutes and then stir vigorously again.				
	Apply the adhesive using a wallpaper machine directly onto the wallcovering or using a short-haired lambskin role in the width of the strips onto the surface. Hang the wallcovering into the damp bed of adhesive und press it down evenly with a moos rubber role or a paper-hanger spatula. Moisten cladded wallcover- ings on the back with a wet sponge before hanging.				
	Hang the wallpaper according to the manufacturer's instructions.				
	Do not use if the object and/or room temperature are below + 5° Celsius! Clean tools with water immediately after use. Remove adhesive residues using a damp cloth				
Mixing ratio:	Way of application	Mixing ratio	Quantity of water per 1 kg packet	Coverage of a 1 kg packet	
	Pre-pasting	1:20	20	approx. 140 m <sup>2</sup>	
	Non woven wallpaper	1:11	11	approx. 60 m <sup>2</sup>	
Storage:	Store in a cool and dry place!				
Available sizes:	500 g collapsible box 1 kg collapsible box	020901000 020902000			