

## PUFAS Wallpaper Adhesive – Special PUFAS Spezialkleister

High-quality super special methyl cellulose adhesive

Instructions for use:	PUFAS Wallpaper Adhesive – Special is a professional adhesive for all vinyl, embossed vinyl, woodchip and embossed wallpapers and heavy wallpapers.			
Technical specifications:	Components:	starch ethe	r, poly vinyl acetate po	owder
	Density:	approx. 0.5	0 g/cm³	
	pH-value:	approx. 8		
	Solubility:	ready for u	se after approx. 30 mi	nutes
	Usage:	approx. 20	0 ml/m²	
Surface preparation:	The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using <i>PUFAS Wallpaper Remover</i> . Make good cracks and holes using <i>PUFAS Interior</i> or <i>PUFAMUR Super Bonding Filler</i> . Pretreat highly absorbent, sanding and chalking surfaces using <i>PUFAS Deeply-Penetrating Primer – solvent free</i> .			
	Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using <i>PUFAS Insulating Spray White</i> .			
	To make a subsequent change of wallpaper easier, we recommend priming the surface first with <i>PUFAS Wallpaper Base Primer 'Tapeten-Wechselgrund'</i> , especially where washable wallpapers are used.			
Application:	Stirring vigorously, sprinkle <i>PUFAS Wallpaper Adhesive</i> – <i>Special</i> into clean, cold water and continue to stir for a few minutes. Leave for 30 minutes and then stir vigorously again.			
	Apply the adhesive to the wallpaper using a brush. Fold the pasted ends in- wards and hang after an adequate soaking time. Always observe the wallpaper manufacturer's instructions for use.			
	We recommend to add 750 g PUFAS Wallpaper and Border Adhesive per 200 g packet PUFAS Wallpaper Adhesive – Special for use on hardly absorbent surfaces and to increase the moisture resistance.			
	Do not use if the surface and room temperature are below + 5° Celsius! Remove adhesive residues using a damp cloth. Clean tools in water after use.			
Mixing ratio:	for	Mixing ratio	Quantity of water per 200-g packet	Coverage of a 200-g packet
	Pre-pasting	1:40	81	60-80 m <sup>2</sup>
	Heavy wallpapers	1:20	41	22-26 m <sup>2</sup>
	Woodchip wallpaper	1:20	4 I	22-26 m <sup>2</sup>
	Special bonding situations	1:15	31	10-15 m <sup>2</sup>
Storage:	Store in a cool and dry place!			
Available size:	200 g collapsible box 000202000			