

PUFAS Wallpaper Power Remover RK

PUFAS Rauhfaser-Kraftlöser RK

- concentrate
- extremely strong removing power
- for overcoated woodchip and heavy wallpapers
- rapid softening of wallpaper
- contains biodegradable surfactants

Instructions for use:

PUFAS Wallpaper Power Remover RK is suitable for easily removing paper, textile, vinyl wallpapers as well as distemper paints. By the excellent stripping power it is possible to remove fast and easily even woodchip wallpapers with several coats of paint and other, similarly hard-to-strip wallcoverings.

Technical specifications:

Components:	ionic and non-ionic tensides
pH-value:	approx. 7-8
Density:	approx. 1.0 g/cm ³
Usage:	depending on the thinning, 250 ml suffice
	for approx. 40 - 50 m ²

Application:

Stir 250 ml PUFAS Wallpaper Power Remover RK in 5 l of water. For lightweight wallpapers the amount of water added can be increased to 10 l. Thin larger quantities with a corresponding ratio. Hot water increases the detaching effect.

Apply the solution, saturating the surface, using a brush or a suitable spray gun and leave for approx. 15 minutes to take effect.

If necessary apply again. The softened wallpapers can then be easily pulled off. Roughen the surface of waterproof and painted wallpapers sing a needle roller or coarse abrasive paper before treating with remover.

To remove distemper paints, apply PUFAS Wallpaper Power Remover RK (thinning 1:60) to the areas, leave to take effect for a short time and then scrape off using a stopping knife. Wash off any residues.

PUFAS Wallpaper Power Remover RK is neutral, stains can be easily removed with water. Subsequent pasting is not impaired.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the surface and/or room temperature are below + 5° Celsius! Clean tools in water after use.

Immediately remove residual adhesive using a damp cloth.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool place! Keep containers tightly sealed!

Available sizes:

4007954067048	006704000	REG
4007954067055	006705000	REG
4007954067062	006706000	REG
	4007954067055	4007954067055 006705000

PUFAS Werk KG - Im Schedetal 1 - 34346 Hann. Muenden - Germany - www.pufas.com Note:

As of 2023-08-29

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.