

## PUFAS Wallpaper Primer – White T8

### PUFAS Tapetengrund Weiß T8

Solvent-free, white pigmented prime coat for balancing out colour differences in surfaces before wallpapering.

**Usage:** *PUFAS Wallpaper Primer - White T8* is ideally suitable for balancing out even extreme colour differences in the surface. It is suitable for all common mineral surfaces as well as gypsum boards, wallpapers and emulsion paints. Especially suited for subsequent wallpapering with translucent or paintable wallpapers as well as for renovation works in which a white background surface is required, e.g. for interior floating and set work.

*PUFAS Wallpaper Primer – White T8* increases the strength of non-firm surfaces and controls the absorbency.

*PUFAS Wallpaper Primer - White T8* is not suitable as a surface for filling compounds containing gypsum or cement.

**Technical specifications:**

Components:	Synthetic resin emulsion, titanium dioxide, additives
Density:	approx. 1.5 g/cm <sup>3</sup>
pH-value:	8-9
Usage:	100 200 ml/m <sup>2</sup> - 10 l suffice for approx. 80 m <sup>2</sup>

**Surface preparation:** Clean the surface of loose material. Pretreat highly absorbent, sanding and chalking surfaces with *PUFAS Deeply-Penetrating Primer – solvent free*. Remove old wallpapers and distemper paints using *Pufas Wallpaper Remover*. Make good cracks and holes using *PUFAS Interior* or *Pufamur Super Bonding Filler*.

**Instructions for use:** *PUFAS Wallpaper Primer – White T8* is ready to use and can be applied using a brush, roller or a suitable spray gun (the max. particle size is 0.2 mm).

*PUFAS Wallpaper Primer - white T8* can be tinted using *PUFAS Tinting Paints* or *pufamix Universal Concentrated Colorants (max. 10 %)* E.g. 2 x 750 ml *PUFAS Tinting Paints* into 10 l *PUFAS Wallpaper Primer – white T8*.

Do not apply any further treatment to surfaces pretreated with *PUFAS Wallpaper Primer – White T8* until they have completely dried. The drying time is approx. 6-8 hours, depending on the absorbency of the surface and room ambient conditions.

Do not use if the surface and/or room temperature are below + 5° Celsius!  
Clean tools in water after use.

**Storage:** Keep containers tightly sealed and store in a cool, but frost-free place.

**Available sizes:**

012901000	2.5 l PE tub
012902000	5 l PE tub
012903000	10 l PE tub