

decotric Modelling Plaster for Construction and Hobbies

decotric Modellgips fuer Bau und Hobby

Pure natural gypsum for handicrafts and repair works

Instructions for use:	<i>decotric Modelling Plaster for Construction and Hobby</i> is suitable for fixing plugs, sockets and other construction elements as well as for filling holes and casting figures.	
Technical specifications:	Components:	natural gypsum
	Density:	approx. 750 g/cm ³
	pH-value:	approx. 7.5
	Mix ratio:	as filler: 2.0-2.2 kg in 1 l water as casting mass: 1.5 kg in 1 l water
	Working time:	approx. 10 minutes
Preparation of surface:	The surface must be dry, firm and free of release agents). Prime highly absorbent, sanding and chalking surfaces with <i>decotric Deeply Penetrating Primer – Solvent Free.</i>	
Application:	Fill clean, cold water into a clean container and sprinkle <i>decotric Modelling Plaster for Construction and Hobby</i> . Stir well, so that a lump free mass is the result. The stirred gypsum mass is approx. 10 minutes usable. Clean tools in water immediately after use.	
Storage:	Store in a cool and dry place!	
Available sizes:	Paper bag of 1.5 kg	003315000
	Paper bag of 5 kg	003313000
	Paper sack of 25 kg	003314000