

pufamur Finish Filler RAK3

pufamur Finish-Spachtel RAK3

- lightweight filler for roller, trowel and airless application
- ready-to-use formulation for all application methods
- easy workability
- application thickness up to 3 mm
- very easy to sand
- CE-compliant to EN 13963-2A

Instructions for use:

Ready to use solvent-free acrylic filler for repairing, skimming and smoothing painted walls and ceilings indoors. Optimal bonding even on non-absorbent emulsion-based surfaces. Ideal for skimming surfaces of paint, glass fabric, synthetic render, mineral surfaces as well as plasterboards, gypsum fibre and dry construction boards.

Technical specifications:

Components: styrene-acrylic emulsion, filling compound, additives
Density: approx. 1.4 g/cm³
pH-value: approx. 8-9
Usage: approx. 1,4 kg per m² depending on layer thickness

Substrate preparation:

The surface must be dry, firm and free of dust, grease and other release agents (e.g. formwork oil). Sandy, chalky and very absorbent surfaces have to be treated first with primer. Repair deep holes and cracks with pufamur super bonding filler SH45.

Application:

Stir well before application which should be done with a smoothing trowel or a roller with a pile height between 15 and 18 mm. When using an airless spraying device (e.g. Euromair EUROPRO 1080, Graco Mark V, Wagner PS 3.39 and equivalent) the base pressure should be 215 bar, working pressure 160 to 180 bar, nozzle size 029 to 041 and the maximal hose length 15 m. After application smooth out the surface with a trowel. For sanding pufamur Finish-Filler RAK3 when dry, use an abrasive with grit size starting from 180. When using a grinding machine avoid giving too much pressure on the surface, use a medium rotation level and ensure that the dust is continuously extracted by an exhaust system or other.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the object and/or room temperature are below + 5° Celsius!

Clean tools in water after use.

Storage:

Store in a cool and dry place.

Store container well sealed!

Available sizes:

22 kg	4007954329047	032904000	REG
-------	---------------	-----------	-----