

PUFAS Ready Mix Filler FS PUFAS Fertigspachtel FS

- for quick repairs
- easy to smooth
- crack-free curing
- very easy to sand
- for indoor use
- CE-compliant to EN 13963-2A

Instructions for use:

PUFAS Ready-Mix Filler FS is ideally suited for repairing, smoothing and coating uneven, rough surfaces as well as for securely filling indoor prefabricated concrete elements, patent plaster and structured plaster surfaces. PUFAS Ready-Mix Filler FS is particularly stable and is ideally suited for smoothing over glass cloth.

Can be used on all mineral surfaces (plaster, concrete, clay tiles, etc.), emulsion paints and plaster boards.

Not suitable for filling wood, metal, glass and plastic.

Technical specifications:

Components: synthetic resin dispersion, fillers, additives, methyl cellulose

Density: approx. 1.8 g/cm³

pH-value: approx. 8 - 9

Usage: approx. 1.7 kg/m² for 1 mm layer thickness

Drying time: 4-7 hours, depending on the thickness of the layer, absorbency of the surface and ambient temperature

Substrate preparation:

The surface must be dry, firm and free of release agents (dust, formwork oil, etc.). Remove old wallpapers and flaking coats of paint with PUFAS Wallpaper Remover TL. Remove loose plaster. Prime highly absorbent, sanding and chalking surfaces with PUFAS Deeply-Penetrating Primer LF – solvent free.

Application:

Apply PUFAS Ready Mix Filler FS up to 5 mm layer thickness. Irregularities can be smoothed when moist or sanded over. Do not apply subsequent coats of paint or adhesive until the filled area has completely dried out. Treat the surface with PUFAS Deeply-Penetrating Primer LF – solvent free before applying synthetic resin based plaster.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the surface and/or room temperature are below + 5° Celsius! Clean tools in water after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool, but frost-free place. Keep the containers tightly sealed!

Available sizes:

400 g	4007954337011	033701000	REG
400 g	4007954337110	033701031	EE