

PUFAS Woodchip Repair Filler RF

PUFAS Rauhfaser Reparatur RF

- textured filler
- perfectly matches ingrain/wood-chip wallpaper texture
- quick-drying
- overcoatable

Instructions for use:

PUFAS Woodchip Repair Filler RF is perfectly suitable for mending dam-aged woodchip wallpapers. Ideal for repairing dowel holes, cracks and similar damaged areas. Thanks to its structure, the filler adapts itself perfectly to the woodchip granulation.

Not suitable for filling work on wood, metal, glass and plastic

Technical specifications:

Components: styrene-acrylate dispersion, filling material, additives, wood fibre
Density: approx. 1.7 g/cm³
pH-value: approx. 8 - 9
Drying period: approx. 1 hour depending on coating thickness, surface absorbing capacity and ambient –temperature

Substrate preparation:

The surface must be dry, stable and free from parting compounds (grease, dust, formwork release oil, etc.). Pre-fill holes and cavities with PUFAS Interior Filler FSI or PUFAMUR Super Bonding Filler SH 45. Pretreat strongly absorbent, sanding or chalking surfaces with PUFAS Deeply-Penetrating Primer LF – solvent free.

Glue open seams of the woodchip wallpapers with PUFAS Seam Adhesive NK..

Application:

Knead tube well before each use. Apply PUFAS Woodchip Repair Filler RF directly from the tube onto the damaged area using a spatula and create the desired surface structure using a spatula or brush. The filled surface can be painted over after complete through drying.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the surface and/or room temperature are below + 5° Celsius! Clean tools in water after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool place! Keep containers tightly sealed!

Available sizes:

330 g 4007954342015 034201000 REG