Technical Information Sheet



Painter Universal Fabric

Maler- und Universalvlies 1 x 25 m Special glass fibre fleece for surface restoration

Instructions for use: Wall and ceiling surfaces riddled with hairline cracks as well as roughly structured

surfaces such as removable plaster, roughcast plaster, glass-fibre fabric and the like can be renovated rationally and effectively using *Painter Universal Fabric*. The surfaces thus obtained are even and perfectly suitable for all further paint

work such as painting, filling, wallpapering, plastering and gluing.

Technical data: Colour: white

Weight per unit area: approx. 35 g/m²
Thickness: approx. 0.35 mm

Surface preparation: The surfaces must correspond to the requirements of the embedding materials

to be used. The surfaces to be renovated must be dry and solid as a general rule. Prime strongly absorbent, sanding and chalking surfaces with *Deeply-Penetrating Primer - solvent free*. The operating instructions of the embedding materials

used must be complied with in any case.

Application: For gluing Painter Universal Fabric, use unfilled dispersion adhesives such as

PUFAS Wallpaper and Border Adhesive or PUFAS Fabric Adhesive or filled adhesives such as PUFAS Styrofoam Adhesive or PUFAS Rigid Foam Adhesive as

well as Pufamur Ready-mix Filler.

The choice of the glue depends on the surface and the work to follow. Unfilled glue can be used for renovating hairline cracks on surfaces which are already smooth. Rough, coarsely structured surfaces require the application of filled adhesives or dispersion type filling compounds.

Apply the wall covering adhesive onto the surface using a roller or apply the filling compound with the aid of a serrated trowel, insert the *Painter Universal Fabric* in

the crease-free, wet adhesive bed and press it on evenly by means of a smoothing trowel or paperhanger's spatula. *Painter Universal Fabric* can be glued in a non-overlapping (butt joint) or overlapping fashion with following overlap & double

cut.

Further working on the renovated surfaces will be possible after they have com-

pletely dried.

Available size: Article no 009602000

EAN 4007954096024 Roll with 25 m x 1 m each