

PUFAS Silicone Joint Sealant S25

PUFAS Silikon-Fugendicht S25

- ideal for sanitary and damp spaces
- fungistatic – with long-term film protection against mould infection
- for up to 25 mm joint widths
- permanently elastic
- UV-stable
- ageing-resistant
- 25 % expansibility
- for indoor and outdoor use
- CE-compliant to EN 15651-1/F-EXT-INT-CC, EN 15651-3/S1
- colours: transparent, white and grey

Instructions for use:

PUFAS Silicone Joint Sealant S 25 - exceptionally suited for permanently-elastic sealing and pointing of connecting joints to 25 mm. For use on substrates such as glass, enamel, porcelain, paint-coated and glazed surfaces, ceramic tiles, metals and non-ferrous metals and PVC. After vulcanisation under humid conditions, the material is UV and weather-resistant, as well as abrasion-resistant. PUFAS Silicon Filler S 25 is provided with a fungicide.

Not suitable for substrates of marble, natural stone, polyethylene, polypropylene and for fish-tanks and underwater joint-filling

Technical specifications:

Components: alcoxim linked Silicon
 Density: approx. 0.98 g/cm³
 pH-value: approx. 2
 ultimate elongation (%): 500
 practical elongation (%): 25
 Skin formation within: (standard temperature)10 minutes
 Temperature resistant: -40°C to 120°C
 Usage: 100 ml/m by 1 cm² joint section

Substrate preparation:

The surface must be dry, stable, firm and free of release agents

Application:

Press PUFAS Silicone Joint Sealant S 25 into the joint to be filled, and smooth off immediately wet. Immediately remove any residues Clean tools with water and household cleaner immediately after use.

Working time: approx. 5 min.

Hardening: approx 3 mm per day

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the surface and/or room temperature are below + 5° Celsius!

Clean tools in water after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool dry place. By transport temperature resistance, -15°C.

Keep container tightly sealed.

Available sizes:

Transparent:

310 ml	4007954349014	034901000	REG
310 ml	4007954348918	034801092	CIS

White:

310 ml	4007954348116	034811000	REG
310 ml	4007954348925	034811092	CIS

Grey:

310 ml	4007954348215	034821000	REG
310 ml	4007954348932	034821092	CIS