

# PUFAS PVC/CV and Carpet Adhesive TE71

## PUFAS Einseitkleber TE71

- for PVC and textile floor coverings
- long-lasting strength
- suitable for chair castors to EN 12529
- suitable for floor heating systems
- for absorbent and non-absorbent substrates
- solvent-free

### Instructions for use:

PUFAS PVC/CV and Carpet Adhesive TE 71 is suitable for gluing PVC/CV coverings, needle felt as well as textile floor coverings with various backings. PUFAS PVC/CV and Carpet Adhesive TE 71 is suitable for chair casters to DIN 68131 and for screeds with floor heating.

### Technical specifications:

Components: terpolymer plastic dispersion, fillers, natural resin ester  
 Density: approx. 1.3 g/cm<sup>3</sup>  
 pH-value: approx. 7 – 8  
 Usage: A2 indentations: 300-350 g/m<sup>2</sup>  
 B2 indentations: 350-450 g/m<sup>2</sup>  
 GEV-EMICODE: EC 1 – very low emission

### Substrate preparation:

The surface must be firm, permanently dry, and free of cracks and release agents. Remove any unevenness using AKAPLAN Floor levelling compound. Prime highly absorbent and sanding surfaces using PUFAS Deeply-Penetrating Primer LF – solvent free.

### Application:

#### Absorbent surfaces

Evenly apply PUFAS PVC/CV and Carpet Adhesive TE 71 on absorbent surfaces or steam permeable floor coverings with a spreading comb (A2 for PVC and foam backings, B2 for jute backings) and leave for dry for 10-20 minutes and then place the flooring in the adhesive bed.

#### Impermeable surfaces:

By PVC-, PVC flooring and other impermeable surfaces leave for dry until the adhesive is completely dry (30-60 minutes) and then place the flooring in the adhesive bed. It is possible to weld PVC floorings after 24 hours.

The ventilation depending on the absorbency of the surface, the ambient temperature and air humidity.

Follow the flooring manufacturer's laying instructions. Immediately remove any adhesive residues with water.

### Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the surface and/or room temperature are below + 10° Celsius!

Clean tools in water after use.

### Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

### Storage:

Store in a cool place! Keep the containers tightly sealed!

### Available sizes:

3 kg	4007954015025	001502000	REG
5 kg	4007954015032	001503000	REG
10 kg	4007954015049	001504000	REG