

PUFAS Rigid-Foam Adhesive HS PUFAS Hartschaumkleber HS

- for insulation board and mouldings, wall decoration and designer features made from rigid foam and polystyrene
- extra-high bond strength
- high initial adhesion
- long-term resistance to damp spaces
- solvent-free

Instructions for use:

PUFAS Rigid-Foam Adhesive HS is ideally suited for bonding decorative, exposed and insulating panels made of polystyrene, Depron or rigid foam and Styrofoam battens and bonding layers.

Technical specifications:

Components: terpolymer plastic dispersion
 Density: approx. 1.66 g/cm³
 pH-value: approx. 9 - 10
 Usage: approx.. 750 g/m²

Substrate preparation:

The surface has to be absorbent, dry, firm and free of release agents (dust, grease, etc.). Remove loose plaster, old wallpaper and loose paint. Make good cracks and holes using PUFAS Interior Filler FSI or PUFAMUR Super Bonding Filler SH 45. Prime strongly absorbent, sanding or chalking surfaces with PUFAS Deeply- Penetrating Primer LF – solvent free.

Application:

Apply PUFAS Rigid-Foam Adhesive HS evenly to the surface with a tooth trowel (preferably B2 toothing). Lay in panels or strips to be bonded and press on evenly. For bondings at ceilings, the adhesive should be applied to the back of the ceiling panels.

When the adhesive has dried completely (1-2 days, depending on absorptive capacity of the surface), the bonded surfaces can be painted, wallpapered or smoothed over. In order to achieve an optimum adhesion of wallpaper to the bonded surfaces, it is recommended to apply a bond-bridging paint with a slurried adhesive (PUFAS Rigid-Foam Adhesive HS with 20 % water added).

Remove adhesive tailings with water immediately.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Remove adhesive residues with water.

Do not use at surface and room temperatures of below + 5 C.

After use, clean tools with water.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool place! Keep containers tightly sealed!

Available sizes:

4 kg	4007954010020	001002000	REG
8 kg	4007954010037	001003000	REG
14 kg	4007954010044	001004000	REG

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.