

Trade name :

Article number : Revision date : Reno-inn Rapid Renovation Paint S130
(Reno-inn Schnell-Renovierfarbe S130)0126__000Version (Revision) :22.07.2020Print date :

5.0.0 (4.6.0) 22.07.2020

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier Reno-inn Rapid Renovation Paint S130 (Reno-inn Schnell-Renovierfarbe S130) (0126_000) 1.2 Relevant identified uses of the substance or mixture and uses advised against **Relevant identified uses** Products Category [PC] PC9a - Coatings and paints, thinners, paint removers Sectors of use [SU] SU21 - Consumer uses: Private households (= general public = consumers) SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) 1.3 Details of the supplier of the safety data sheet Supplier (manufacturer/importer/only representative/downstream user/distributor) PUFAS Werk KG Street : Im Schedetal 1 Postal code/city: 34346 Hann. Münden Telephone: +49 (0)5541 7003-01 Telefax: +49 (0)5541 7003-50 Information contact :

E-mail (competent person) : <u>sds@pufas.de</u> Website : <u>www.pufas.de</u>

1.4 Emergency telephone number +49 (0)5541 7003-41/-64

Only available during office hours (Mo-Th 8 - 16 h, Fr 8 - 12.30 h).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 [CLP] Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

2.2 Label elements Labelling according to Regulation (EC) No. 1272/2008 [CLP]



Flame (GHS02) Signal word Warning Hazard components for labelling HYDROCARBONS C4, 1,3-BUTADIENE-FREE, POLYMD., TRIISOBUTYLENE FRACTION, HYDROGENATED ; CAS No. : 93685-81-5 HYDROCARBONS C10-C12, ISOALKANES, < 2% AROMATICS



Trade name :	Reno-inn Rapid Renovation Paint S130 (Reno-inn Schnell-Renovierfarbe S130)		
Article number :	0126000	Version (Revision) :	5.0.0 (4.6.0)
Revision date :	22.07.2020	Print date :	22.07.2020

Hazard statements	
H226	Flammable liquid and vapour.
Precautionary stater	nents
P102	Keep out of reach of children.
P262	Do not get in eyes, on skin, or on clothing.
P280	Wear protective gloves/eye protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P260	Do not breathe vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P101	If medical advice is needed, have product container or label at hand.
P403+P235	Store in a well-ventilated place. Keep cool.
P370+P378	In case of fire: Use foam to extinguish.
P501	Dispose of contents/container in accordance with local/regional/national regulations of waste disposal.
Supplemental Hazar	d information (FII)

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

This mixture does not contain any substances classified as PBT/vPvB or included in the SVHC-Candidate List.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Consists of: Acrylic resin, extenders, titan dioxide, solvent and additives

Hazardous ingredients

 HYDROCARBONS C10-C12, ISOALKANES, < 2% AROMATICS ; REACH No. : 01-2119471991-29 ; EC No. : 923-037-2</td>

 Weight fraction :
 $\geq 10 - < 15 \%$

 Classification 1272/2008 [CLP] :
 Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 Aquatic Chronic 4 ; H413

 HYDROCARBONS C4, 1,3-BUTADIENE-FREE, POLYMD., TRIISOBUTYLENE FRACTION, HYDROGENATED ;

 REACH No. : 01-2119490725-29 ; EC No. : 297-629-8; CAS No. : 93685-81-5

 Weight fraction :
 $\geq 10 - < 15 \%$

 Classification 1272/2008 [CLP] :
 Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Notice the directions for use on the label. When in doubt or if symptoms are observed, get medical advice. Change contaminated, saturated clothing.

Following inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Page : 2 / 9



Trade name :

Article number : Revision date : Reno-inn Rapid Renovation Paint S130
(Reno-inn Schnell-Renovierfarbe S130)0126__000Version (Revision) :22.07.2020Print date :

5.0.0 (4.6.0) 22.07.2020

After ingestion

Observe risk of aspiration if vomiting occurs. Do NOT induce vomiting. Call a physician in any case!

4.2 Most important symptoms and effects, both acute and delayed No information available.

4.3 Indication of any immediate medical attention and special treatment needed None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water mist alcohol resistant foam Carbon dioxide (CO2) Extinguishing powder

Unsuitable extinguishing media

Full water jet Strong water jet

5.2 Special hazards arising from the substance or mixture

5.3 Advice for firefighters

None

Special protective equipment for firefighters

Do not inhale explosion and combustion gases. In case of fire: Wear self-contained breathing apparatus.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

The usual precautionary measures for the handling of chemicals have to be observed. Provide adequate ventilation. Remove all sources of ignition. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Normal precautions taken when handling chemicals should be observed. Avoid contact with skin and eyes. Keep away from food, drink and animal feeding stuffs.

Measures to prevent fire

Only use the material in places where open light, fire and other flammable sources can be kept away. Provide adequate ventilation as well as local exhaustion at critical locations. Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.



Trade name :	Reno-inn Rapid Renovation Paint S130 (Reno-inn Schnell-Renovierfarbe S130)		
Article number :	0126000	Version (Revision) :	5.0.0 (4.6.0)
Revision date :	22.07.2020	Print date :	22.07.2020

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep/Store only in original container. Keep container tightly closed.

Further information on storage conditions

Do not store outside. Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Please note safety instructions and directions for use on the drum. **Recommended storage temperature :** Store it seperately from foods.

7.3 Specific end use(s)

Recommendation

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Suitable eye protection goggles

Skin protection

Hand protection

Gloves(tested for example according to EN374) made of the following materials used by hand contact with the product: Nitrile rubber (NBR)

Thickness of the gloves: > 0.4 mm

Breakthrough time: >= 8h

After washing hands replace lost skin fat by fat containing skin creams.

Body protection

Wearing of closed working clothes. Remove contaminated, saturated clothing.

Respiratory protection

Suitable respiratory protection apparatus

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

General information

The usual precautionary measures for the handling of chemicals have to be observed. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

Environmental exposure controls

See also section 6 and 12.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : liquid: viscous Colour : white



Trade name :	Reno-inn Rapid Renovation Paint S130 (Reno-inn Schnell-Renovierfarbe S130)		
Article number :	0126000	Version (Revision) :	5.0.0 (4.6.0)
Revision date :	22.07.2020	Print date :	22.07.2020

Odour

characteristic

Safety characteristics

 Melting point/freezing point :	(1013 hPa)		No data available		
Initial boiling point and boiling range :	(1013 hPa)	>	35	°C	
Flash point :			43	°C	Brookfield
Auto-ignition temperature :		>	200	°C	
Lower explosion limit :		approx.	0,6	Vol-%	
Upper explosion limit :		approx.	19	Vol-%	
Vapour pressure :	(50 °C)	approx.	50	hPa	
Vapour pressure :	(20 °C)		1	hPa	
Density :	(20 °C)	approx.	1,2	g/cm ³	
Solvent separation test :	(20 °C)	<	3	%	
Flow time :	(20 °C)	>	90	S	DIN-cup 4 mm
Solid content :		approx.	70	Wt %	
Solvent content :		approx.	28	Wt %	
VOC-value :			345	g/l	
Other information					

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions No information available.

10.4 Conditions to avoid No information available.

10.5 Incompatible materials None, if handled according to order.

10.6 Hazardous decomposition products

Gases/vapours, flammable

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Exposure route Species : Effective dose :

Parameter : Exposure route Species : Effective dose : Parameter :

No data available

Acute oral toxicity

CILY	
	LD50 (HYDROCARBONS C10-C12, ISOALKANES, < 2% AROMATICS)
:	Oral
	Rat
1	> 5000 mg/kg
	LD50 (HYDROCARBONS C4, 1,3-BUTADIENE-FREE, POLYMD., TRIISOBUTYLENE FRACTION, HYDROGENATED ; CAS No. : 93685-81-5)
:	Oral
	Rat
1	> 5000 mg/kg



Trade name :	Reno-inn Rapid Reno (Reno-inn Schnell-Re					
Article number :	0126000	Version (Revision) :	5.0.0 (4.6.0)			
Revision date :	22.07.2020	Print date :	22.07.2020			
Practical experi	ence/human evidence					

This product is unlikely to	o harm health, given normal and proper handling and hygienic precautions.
Acute dermal toxicity	
Parameter :	LD50 (HYDROCARBONS C10-C12, ISOALKANES, < 2% AROMATICS)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 5000 mg/kg
Parameter :	LD50 (HYDROCARBONS C4, 1,3-BUTADIENE-FREE, POLYMD., TRIISOBUTYLENE FRACTION, HYDROGENATED ; CAS No. : 93685-81-5)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 5000 mg/kg
Acute inhalation toxicity	1
Parameter :	LC50 (HYDROCARBONS C10-C12, ISOALKANES, < 2% AROMATICS)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	> 5000 mg/m ³
Exposure time :	8 h
Parameter :	LC50 (HYDROCARBONS C4, 1,3-BUTADIENE-FREE, POLYMD., TRIISOBUTYLENE FRACTION, HYDROGENATED ; CAS No. : 93685-81-5)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	> 5000 mg/m ³
Exposure time :	8 h
Corrosion	
No data available	
Respiratory or skin s	sensitisation
No data available	
•	city (subacute, subchronic, chronic)
No data available	
CMR effects (carcino	ogenicity, mutagenicity and toxicity for reproduction)
Carcinogenicity	
No data available	
Germ cell mutagenicity	
No data available	
Reproductive toxicity	
No data available	
STOT-single exposu	re
No data available	
	osure
	osure
STOT-repeated expo No data available	osure
STOT-repeated expo No data available Aspiration hazard	
STOT-repeated expo No data available Aspiration hazard Harmful: may cause lung d	amage if swallowed.
STOT-repeated expo No data available Aspiration hazard Harmful: may cause lung d Additional informatio	amage if swallowed.

SECTION 12: Ecological information

12.1 Toxicity

11.5

No information available.



Trade name :

Article number : Revision date : Reno-inn Rapid Renovation Paint S130
(Reno-inn Schnell-Renovierfarbe S130)0126__000Version (Revision) :22.07.2020Print date :

5.0.0 (4.6.0) 22.07.2020

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances classified as PBT/vPvB or included in the SVHC-Candidate List.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Additional information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Dispose according to legislation. Handle contaminated packages in the same way as the substance itself. **Waste codes/waste designations according to EWC/AVV**

Waste code product

Not used: 08 01 11 Drying up: 08 01 12 **Waste name** Not used: waste paint and varnish containing organic solvents or other dangerous substances Drying up: waste paint and varnish other than those mentioned in 08 01 11 **Waste code packaging** 15 01 04 **Waste name** metallic packaging

SECTION 14: Transport information

14.1 UN number

UN 1263

14.2 UN proper shipping name

Land transport (ADR/RID) PAINT Sea transport (IMDG) PAINT Air transport (ICAO-TI / IATA-DGR) PAINT



Trade name :	Reno-inn Rapid Renovation Paint S130 (Reno-inn Schnell-Renovierfarbe S130)		
Article number :	0126000	Version (Revision) :	5.0.0 (4.6.0)
Revision date :	22.07.2020	Print date :	22.07.2020

14.3 Transport hazard class(es)	
Land transport (ADR/RID)	
Class(es) :	3
Classification code :	F1
Hazard identification number (Kemler	
No.):	30
Tunnel restriction code :	D/E
Special provisions :	LQ 5 I \cdot E 1 \cdot Transport in containers with max. 450 litres contents are not subject to the regulations of ADR/RID.
Hazard label(s) :	3
Sea transport (IMDG)	
Class(es) :	3
EmS-No. :	F-E / <u>S-E</u>
Special provisions :	LQ 5 · E 1 · IMDG 2.3.2.5 (<= 30)
Hazard label(s) :	3
Air transport (ICAO-TI / IATA-DGR)	
Class(es) :	3
Special provisions :	E 1
Hazard label(s) :	3
14.4 Packing group	
14.5 Environmental hazards Land transport (ADR/RID): No Sea transport (IMDG): No Air transport (ICAO-TI / IATA-DGR):	Νο
14.6 Special precautions for user None	
not applicable	Annex II of Marpol and the IBC Code
14.8 Additional information	
This product is not subject to the ADR, Cla	iss 3, see ADR, Chapter 2.2.3.1.5.

SECTION 15: Regulatory information

^{15.1} Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Labelling for contents according to regulation (EC) No. 648/2004

- this product is not subject to EC Detergent regulation no. 648/2004.

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

- EU limit value for this product (cat. A/g, SB): 350 g/l (2010)
- VOC-Gehalt dieses Produktes max.: 345 g/l

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

15.3 Additional information

None



Trade name :	Reno-inn Rapid Renovation Paint S130 (Reno-inn Schnell-Renovierfarbe S130)		
Article number :	0126000	Version (Revision) :	5.0.0 (4.6.0)
Revision date :	22.07.2020	Print date :	22.07.2020

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Label elements · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Supplemental Hazard information (EU)

16.2 Abbreviations and acronyms

None

- **16.3 Key literature references and sources for data** None
- ^{16.4} Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H226 Flammable liquid and vapour.

- H304 May be fatal if swallowed and enters airways.
- H413 May cause long lasting harmful effects to aquatic life.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.