

PUFAS Joint Repair white PUFAS Fugen Reparatur

- special white grout for wall tiles
- ideal for repairing damaged tile joints
- ready-to-use
- crack-free curing
- waterproof – for kitchens and bathrooms

Instructions for use:

PUFAS Joint Repair white is perfectly suitable for repair work on joints of ceramic and glass tiles, tiles and mosaics.

PUFAS Joint Repair white is not suitable for floors.

Technical specifications:

Components: styrene-acrylate dispersion, filling material and additives

Colour: white

Density: approx. 1.8 g/cm³

pH-value: approx. 9 - 10

Substrate preparation:

The joints to be repaired must be dry, stable and free from parting compounds (dust, grease, soap residues, etc.). Remove loose material from the joints by scraping them out.

Application:

Knead tube well before each use. Press PUFAS Joint Repair white directly into the damaged places and carefully remove any protruding filler using a rubber spatula, for instance. The repaired joint must be filled in without any gaps. The tiles need to be cleaned using a damp cloth or sponge before the filler has fully dried through.

Porous, matte and unglazed tiles must be covered before grouting (e.g. with adhesive tape). The mends will be waterproof once PUFAS Joint Repair white has fully dried.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use at surface and room temperatures if below +5° C.

Clean tools with water immediately after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Keep in a cool and frost-free place. Keep the containers tightly sealed!

Available sizes:

400 g	4007955042013	004201001	REG
400 g	4007954042120	004201031	EE

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.