

aka Wallpaper Adhesive Normal aka Tapetenkleister Normal

Economy priced wallpaper adhesive, quality-tested.

Instructions for use: *aka Wallpaper Adhesive Normal* is suitable for pasting lightweight wallpapers.

Technical specifications:

Components:	carboxy methyl cellulose, starch ether
Density:	approx. 0.40 g/cm ³
pH-value:	approx. 8
Solubility:	ready for use in 30 minutes
Usage:	approx. 200 ml/m ²

Surface preparation: The surface must be dry, firm, dust and free of release agents (dust, grease, etc.) Remove all old, loose wallpapers and distempers using *PUFAS Wallpaper Remover*. Make good cracks and holes using *PUFAS Interior* or *PUFAMUR Super Bonding Filler*.

Pre-treat strongly absorbent, abrasive and chalky surfaces with *PUFAS Deeply-Penetrating Primer – solvent free*. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *PUFAS Insulating Spray*. We recommend a first coat with *PUFAS Wallpaper Primer-White* if hanging highly translucent wallpapers and where surfaces are highly contrasting.

Instructions for use: Stirring vigorously, sprinkle *aka Wallpaper Adhesive Normal* into clean, cold water (see table) and continue to stir for a few minutes. Leave for approx 30 minutes and then stir vigorously again.

Evenly apply *aka Wallpaper Adhesive Normal* to the wallpaper using a brush or wallpapering machine, fold the pasted ends inwards and hang after an adequate soaking time. Hang the wallpaper according to the manufacturer's instructions.

Clean tools with water immediately after use.
Do not use if the object and/or room temperature are below + 5° Celsius!
Remove adhesive residues using a damp cloth

Mixing ratio:

for	Mixing ratio	Quantity of water per 125 g packet	Coverage of a 125 g packet
Pre-pasting	1:65	8 l	50-60 m ²
Lightweight wallpapers	1:48	6 l	35 m ²
Heavy wallpapers	1:40	5 l	30 m ²

Storage: Store in a cool and dry place!

Available size: 125 g collapsible box