

extra Wallpaper Adhesive Normal extra Tapetenkleister Normalkleister

Instructions for use: extra Wallpaper Adhesive Normal is suitable for pasting light to medium weight

wallpapers.

Technical specifications: Components: carboxymethyl cellulose, starch ether

Apparent density: approx. 0.40 g/cm³

pH-value: approx. 8

Solubility: ready to use in 30 minutes

Usage: approx. 200 ml/m²

Surface preparation: The surface must be dry, firm, dust and grease free. Remove all old, loose

wallpapers and distempers using *PUFAS Wallpaper Remover*. Make good cracks and holes with *PUFAS Interior* or *PUFAMUR Super Bonding Filler*.

Pre-treat highly absorbent, sanding and chalking surfaces with *PUFAS Deeply-Penetrating Primer – solvent free*. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *PUFAS Insulating Spray White*. We recommend applying a sub-coat of *PUFAS Wallpaper Primer-White* before hanging highly translucent wallpapers and

where surfaces are highly contrasting.

Application: Stirring vigorously, sprinkle extra Wallpaper Adhesive Normal into clean, cold

water and continue to stir for a short time. Leave for 30 minutes and then stir

vigorously again.

Evenly apply the adhesive to the wallpaper using a brush. Fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpa-

per manufacturer's instructions for use.

Do not use if the surface and room temperature are below + 5° Celsius!

Remove adhesive residues using a damp cloth.

Clean tools in water after use.

Mixing ratio: Mixing Quantity of water Coverage of a

for	ratio	per 125 g packet	125 g packet
Pre-pasting	1:80	10 I	60-80 m ²
Lightweight wallpapers	1:52	6.5 l	35 m²
Heavy wallpapers	1:48	6.0 I	30 m²

Storage: Store in a cool and dry place!

Available size: 125 g collapsible box 000808080