

## extra Wallpaper Adhesive Special extra Spezialkleister

**Instructions for use:** *extra Wallpaper Adhesive Special* is suitable for pasting woodchip wallpapers, paper wallpapers, vinyl wallpapers, embossed vinyl wallpapers and all other heavy wallpapers.

**Technical specifications:**

Components:	starch ether, poly vinyl acetate powder
Density:	approx. 0.50 g/cm <sup>3</sup>
pH-value:	approx. 8
Solubility:	ready for use after approx. 30 minutes
Usage:	approx. 200 ml/m <sup>2</sup>

**Surface preparation:** The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using *PUFAS Wallpaper Remover*. Make good cracks and holes using *PUFAS Interior* or *PUFAMUR Super Bonding Filler*.

Pretreat highly absorbent, sanding and chalking surfaces using *PUFAS Deeply-Penetrating Primer – solvent free*. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *PUFAS Insulating Spray White*.

We recommend applying a sub-coat of *PUFAS Wallpaper Primer- White* before hanging highly translucent wallpapers and where surfaces are highly contrasting.

To make a subsequent change of wallpaper easier, we recommend priming the surface with *PUFAS Wallpaper Base Primer 'Tapeten-Wechselgrund'*, especially when hanging washable wallpapers.

**Application:** Stirring vigorously, sprinkle *extra Wallpaper Adhesive Special* into clean, cold water (see table) and continue to stir for a few minutes. Leave for approx. 30 minutes and then stir vigorously again.

Apply the adhesive to the wallpaper using a brush. Fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpapering machine and wallpaper manufacturer's instructions for use.

We recommend to add 750 g *PUFAS Wallpaper and Border Adhesive* per 200 g packet *extra Wallpaper Adhesive Special* for use on hardly absorbent surfaces and to increase the moisture resistance.

Clean tools with water immediately after use.  
Do not use if the object and/or room temperature are below + 5° Celsius!  
Remove adhesive residues using a damp cloth.

**Mixing ratio:**

for	Mixing ratio	Quantity of water per 200-g packet	Coverage of a 200-g packet
Pre-pasting	1 : 40	8 l	60-80 m <sup>2</sup>
Heavy wallpapers	1 : 20	4 l	22-26 m <sup>2</sup>
Woodchip wallpaper	1 : 20	4 l	22-26 m <sup>2</sup>
Special bonding situations	1 : 15	3 l	10-15 m <sup>2</sup>

**Storage:** Store in a cool and dry place!

**Available size:** 200 g collapsible box 002901002