

PUFAS Water STOP WS

Brushable sealing compound

Use:

For repairing leaks in any part of roof. Readily bridges cracks and holes up to 10 mm wide, even in damp weather or snow. Adheres to virtually all substrates (though excluding polystyrene). Waterproof immediately after application. UV-, weather- and ageing-resistant. Resistant to saltwater and diluted alkalis.

Properties:

- permanently elastic
- fibre-reinforced
- UV- and weather-resistant
- immediately waterproof – irrespective of weather
- also adheres to wet substrates
- crack-bridging up to 10 mm
- colour: grey
- overcoatable

Technical data:

Raw material base: Modified alkyd resins, synthetic fibres, fillers, solvents and auxiliary materials

Density: Approx. 1.05 g/cm³

Substrates:

Roofing felt, torch-on membranes, bitumen, fibre cement, aluminium, zinc, lead, copper, metal sheet, roof tiles, shingles, slate, wood, concrete, glass, floor/wall tiles, marble, polycarbonate, acrylic glass, masonry.

Application:

Remove dirt, moss, green growth, leaves, grease, oil and, where necessary, ice sheets from substrate. Slightly roughen smooth surfaces. Pretreat friable and porous substrates with PUFAS Hydrosol Primer Deep-Penetrating LF.

PUFAS Water STOP WS is supplied ready-for-use and shall not be diluted. Stir well prior to use. Apply with a wide brush or spatula. If necessary, apply second coat after drying.

After 12–24 hours (depending on weather), treated surface is ready for subsequent operations, e.g. overcoating with acrylic paint. Application temperature: -10 °C to +35 °C. Cover larger leaks with PUFAS Painter and Repair Fabric.

Consumption:

Approx. 1.5 ltr per m²

Note:

Not suitable for natural stone or as waterproof membrane subject to hydrostatic pressure. Close tubs immediately after use. Wash tools with PUFAS Paint Brush Cleaner R 120 immediately after use.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at www.pufas.de or from sds@pufas.de.

Storage:

Store in cool place in properly sealed containers. Keep out of reach of children.

Disposal:

Do not allow to enter drains, sewers or surface waters. Hand over only fully emptied containers for recycling. Dispose of liquid waste under EWC waste code: 08 04 09.

Item No.	EAN	Container size
012802000	4007954128022	750 ml
012805000	4007954128053	5 ltr



Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.