

PUFAS Euro 3000 Ekonom Universal wallpaper adhesive

PUFAS Euro 3000 Universal Tapeten-Kleber

- for all types of lightweight vinyl, textured, non-woven and paper-backed wallpapers
- dries to transparent finish
- ready to use after 5 minutes
- no lump formation

Instructions for use:

PUFAS EURO 3000 Ekonom Universal wallpaper adhesive is ideally suitable for pasting light and heavy woodchip wallpapers, paper wallpapers and vinyl wallpapers on mineral surfaces and gypsum boards.

Technical specifications:

Components: starch ether, poly vinyl acetate powder
 Density: approx. 0.3-0.4 g/cm³
 pH-value: approx. 8-9
 Usage: approx. 200 g/m²

Substrate preparation:

The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using PUFAS Wallpaper Remover. Make good cracks and holes using *PUFAS Interior Filler FSI* or *pufamur Super Bonding Filler SH45*. Pretreat highly absorbent, sanding and chalking surfaces using *PUFAS Hydrosol Primer Deep-Penetrating LF*.

Application:

Stirring vigorously, sprinkle *PUFAS EURO 3000 Ekonom Universal wallpaper adhesive* into clean, cold water and continue to stir for some minutes. Leave for approx. 5 minutes and then stir vigorously again.

Always observe the wallpaper manufacturer's instructions for use.

Remove adhesive residues using a damp cloth.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the object and/or room temperature are below + 5° Celsius!

Clean tools in water after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool and dry place.

Available sizes:

200 g	4007954220900	022007092	REG
300 g	4007954220924	022002092	REG
500 g	4007954220931	022003092	REG
1 kg	4007954220948	022004092	REG

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.